

NOTE:					NEXT ASSEMBLY				REFERENCE DRAWING			
1. A COPY OF THIS DWG, REDUCED TO 1/4 SIZE,				FINAL					FR0015			
IS TO BE KNO SHIPPED WITH												
2 COVER WIRE CONNECTIONS TO CONNECTOR			E	3.5"	" 31ST301800			Sł	SHRINK TUBING			5
E USING SHRINK TUBING, ITEM 5 (REF)			Ē	1"	31STDW3750			Sł	SHRINK TUBING			4
				AR	AR 1300060/40				SOLDER			3
ELECTRICAL CONNECTIONS			F	1	1 10MSWK0407				CONNECTOR	{	(CANNON NO. WKA7-21C-3/8)	2
CABLE	PIN		_			122007S003			CABLE, BELDEN NO. 8427			1
COLOR	NO.				PA	PART NO.			DESCRIPTION			ITEM
RED	1		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		REVISION	S	A3 CABLE ASSEMBLY, MODEL: 2XX WITH 'BM' CONNECTOR					
GREEN	2		TOLERANCES ON: FRACTIONS ±1/64	LE		BY ECN						
BLACK	3		.XX ±.01 .XXX ±.005	F		SN 9301 FS 11378						
WHITE	4		ANGLES ±1/2° 63 MACHINE FINISH (ALL SURFACES)				SCALE		MATERIAL		DRAFTSMAN DATE	
BLUE	5		REMOVE BURRS & BREAK SHARP EDGES .015 MAX. MACHINE FILLETS TO .015 R. MAX. ALL				1/1 SEE ENGINEERII	NG CHANGE	SEE B/I		RJ 5-21-75	
BROWN	6	DIAMETERS TO BE CONCENTRIC WITHIN.010 F.J.M. CHAMFER ALL MALE THREADS 45°±5° TO MINOR DIAMETER C'SINK ALL FEMALE THREADS 90°±10° TO MAJOR DIAMETER		THIRD ANGLE PROJECTION								
YEL/ORG	7						Corporation WHEATFIELD, New YORK USA			30007		