

PRESSURE TRANSMITTER

Model 970



FEATURES

- **HART® communication**
- **Small size and weight**
- **High pressures**
- **Accuracy to 0.1% FSO**
- **100 PSI up to 100K PSI**

TYPICAL APPLICATIONS

- **Offshore oil rigs**
- **Oil production platforms**
- **Natural gas pipelines**
- **Rig safety systems**

SMART, RANGEABLE, RUGGED

If Rig Real Estate is an issue, then the Model 970 is a great solution. Small sized, this rugged transducer is perfect for Offshore Oil Rigs where space is valuable.

HART® COMMUNICATIONS

HART® communications allow simpler systems commissioning at start up. Digital compensation, done at Viatran to each Model 970, provides excellent accuracy and enhanced rangeability.

REMOTE CALIBRATION

The HART® communication system allows for simultaneous analog and digital communication. This means the Model 970 is fully compatible with existing analog systems while still offering the benefits of digital/remote calibration and communications. Communicating with the 970 can be accomplished with a handheld device or using a PC and available software.

OPTIONAL APPROVALS

The Model 970 is all welded stainless steel which makes it perfect for corrosive environments. It can also have FM, CSA and ATEX hazardous location markings.

MODIFICATION FOR YOUR NEEDS

We can easily modify the Model 970 (and have) for your unique pressure application. Give us a call. You'll find that this pressure transducer is an excellent long-term solution.

For more information, contact Viatran.



Viatran

38 Forge Parkway
Franklin, MA 02038 USA

Hotline: 1-800-688-0030
Phone: 1-716-629-3800
Fax: 1-716-693-9162
Email: solutions@viatran.com
Web: www.viatran.com

PERFORMANCE

Full Scale Pressure Range	0-100 thru 0-100K, PSIA, PSIS
Turndown ($\leq 20K$ PSI)	4:1 with no degradation in static accuracy or thermal effect
Static Accuracy	$\leq \pm 0.1\%$ FSO (combined linearity, hysteresis and zero repeat)
.....	$\leq \pm 0.25\%$ FSO (Ranges 25,000 PSI & Up)
Compensated Range.....	-20°F to 170°F (28°C to 76°C)
.....	$\leq \pm 0.1\%$ span/ $\pm 50^\circ\text{F}$ (relative to 75°F at 1:1 range)
Thermal Error	$\leq \pm 0.35\%$ from -20°F to 170°F (28°C to 76°C)
.....	$\leq \pm 1\%$ per 100°F (25,000 PSI and up)
Full Scale Output (FSO)	16 mA $\pm 0.1\%$ FSO
.....	16 mA $\pm 0.5\%$ FSO
Dynamic Response Time	≤ 300 mSec to reach 63% FSO
Temperature Range, Fluid.....	-40°F to 250°F (-40°C to 121°C)
Storage Temperature Range	-65°F to 250°F (-54°C to 121°C)

ELECTRICAL

Supply Voltage.....	11.5 to 28 Vdc normal operation; 13 to 28 Vdc HART Communication
Power Supply Regulation	$\pm 0.02\%$ FSO per volt
Output Signal	Two wire 4-20 mA. Digital process signal super-imposed on a 4-20
.....	mA signal, available to any HART protocol computer system
Load Impedance	230 Ohms to 1100 Ohms for HART communication
Circuit Protection	Reverse polarity protected
Insulation Resistance	≥ 200 MegOhms to all terminals in parallel and at the transmitter
.....	case
RFI/EMI Supression.....	Negligible to 500 MHz at 5 watts direct contact
Electrical Connection.....	1/2" NPT (M), 3 wires, 18 AWG, 72"L
Red.....	+Power/Signal
Black	-Power/Signal
Green.....	Case Ground

MECHANICAL

Pressure Connection	0-100 thru 0-15K.....	1/4" NPT (F)
	0-20K thru 0-50K.....	1/4" F250-C high pressure tube
	0-60K thru 0-100K.....	5/16" F312-C high pressure tube
Proof Pressure	0-100 thru 0-15K.....	1.5 times or 20K PSI, whichever is less
	0-20K thru 0-100K.....	1.2 times FSPR
Burst Pressure	0-100 thru 3K.....	5 times FSPR
	5K	4 times FSPR
	7.5 thru 10K	2.7 times FSPR
	15K	2.3 times FSPR
	20K	2 times FSPR
	25K thru 100K	1.5 times or 125,000 PSI, whichever is less

MATERIALS OF CONSTRUCTION

Wetted Materials	0-100 thru 0-15K PSI.....	15-5PH, stainless steel
	0-20 thru 0-100K PSI.....	13-8 Mo
Housing	0-100 thru 0-15K PSI.....	316, 15-5PH stainless steel
	0-20 thru 0-100K PSI.....	316 SS and 13-8 Mo
	Shock Limitation.....	100 g's
	Weight	24 oz ± 3 oz
	Identification.....	Laser etched onto body
	Mounting.....	May be mounted by process piping, electrical conduit, or optical
		mounting bracket to 2" pipe

ACCESSORIES

Mounting bracket
Polyhead conduit connection box
HART communicator
In-line remote seals

CERTIFICATIONS (Consult Factory for Available Options)

FM	Intrinsic Safety: Class I, II, III, Division 1, Groups A-G, Class I, Zone 0, AEx ia IIC, T4 at Ta=80°C, T5 at Ta=40°C Entity, Type 4X hazardous locations Explosion Proof: Class I, II, III, Division 1, Groups A-G, AEx d IIC, T5 at Ta=88°C NEMA 4X hazardous locations Nonincendive: Class I,II,III Division 2, Groups A,B,C,D,F,G, Class I, Zone 2, Group IIC, T4 at Ta=80°C T5 at Ta=40°C, Type 4X hazardous locations Nonincendive: Class I,II,III Div. 2, Groups A-G and Class I, Zone 2, Group IIC, T4 at Ta=80°C, T5 at Ta=40°C
CSA	Intrinsic Safety: Ex ia IIC; Class I, Zone 0; Class I, II, III, Groups A-G; Type 4, T4 at Ta=80°C, T5 at Ta=40°C Explosion Proof: Ex d IIC; Class 1, Zone 1, Class I, II, III, Groups A-G, Type 4, T5 at Ta=80°C Hazardous Locations. Nonincendive: Ex nA IIC; Class I, Zone 2, Class I, Div 2, Groups A,B,C,D, Class II, Div 2, Groups F, G, Class III, Div 2, T4 at Ta=60°C, Type 4 Enclosures
ATEX	Intrinsic Safety: II 1 G Ex ia IIC T4 (-20°C < Ta < 50°C) Flameproof: II 2 G Ex d IIC, T6 (-20°C < Ta < 40°C) Type N: II 3 G Nonincendive: Ex nL IIC T4 (-20°C < Ta < 60°C)
CE	PED Directive 97/23/EC EMC Directive 89/336/EEC EN 61326: EMC Conformity Standard

OPTIONS

Codes	CLExtra lead length
	DFBleed port (10K PSI and below)
	DQOxygen cleaning
	EASpecial calibration
	MECSA Explosion Proof label
	NGATEX Flameproof label
	NHCustomer specified information
	NJCE label
	NKATEX Intrinsic Safety/Nonincendive label
	NXCSA Intrinsic Safety label
	NYFM Explosion Proof/Dust Ignition Proof label
	NZFM Nonincendive label
	TFFM Intrinsic Safety label
	TJCSA Div/Zone 2 label
	TKATEX Type N label
	YI1/8" NPT (F)
	YM1/4" F250-C high pressure tube (standard on 20K-50K ranges)
	YN3/8" NPT (F)
	YR1/2" NPT (F)
	YS3/8" F375-C high pressure tube (0-60K max pressure)
	For exotic metal options, consult factory for media, price & delivery
	ZAG 1/2M conduit connection
	ZCCable gland connection
	ZUDirect coupled cable

Note: Application of some available options may affect standard performance. Consult your Viatran representative for details.

