

Pressure Transducer

LOW RANGE GAGE & ABSOLUTE PRESSURE

MODEL 244 / 344



The Model 244 provides a 0 to 5 VDC signal, while the Model 344 offers a 4 to 20 mA signal. Using our variable capacitance technology, the 244 and 344 transducers provide extreme overpressure protection up to 500 PSI.

This sensor design provides standard accuracy of $\leq \pm 0.15\%$ FSO. The unit also offers standard temperature performance to $\pm 2\%/100^\circ\text{F}$ with an improved option to $\pm 1\%/100^\circ\text{F}$.

All wetted surfaces of the X44 Series are constructed with 316 stainless steel, making them ideal for wet/wet applications. In environmental test chambers, these surfaces withstand contaminants such as water vapor, oil, exhaust or mists. Atmospheric reference is specially constructed to withstand the ingress of moisture, ensuring accurate pressure measurement.

Models 244 and 344 feature an internal calibration circuit for easy field setup, a quick disconnect electrical connection and external zero and span controls. These features allow you to calibrate the transducer without an

external pressure source and eliminate the need to send the unit to a metrology lab for calibration.

The small size enables a better fit into tight test applications. Viatran can also easily modify the X44 Series with optional outputs, electrical connectors and pressure ports to suit your application needs.

Viatran has developed a complete family of precision products designed specifically for industrial test and research applications. The X45 and X49 are our most accurate (2 to 100K PSI) gage and absolute units. Models X46 are designed to measure barometric pressure to within 0.01" Hg. For differential pressure measurement, our Models X74 and X76 maintain the same high quality and integrity as our gage and absolute products. You can depend on Viatran's pressure measurement products for the best results.

Viatran's Models 244 and 344 add a low range gage pressure transducer to our extensive industrial test product line. The X44 Series features highly accurate pressure measurement in ranges from 5" W.C. to 100 PSIG.

FEATURES

- 500 PSI overpressure protection
- All 316 SS wetted surfaces
- High accuracy $\leq \pm 0.15\%$
- Very low ranges to 5" WC
- Internal shunt calibration circuit

TYPICAL APPLICATIONS

- Autoclave Systems
- Leak detection systems
- Engine test stands
- Environmental test chambers

Contact Viatran for approval options

For product availability, or to order please call 1-800-688-0030

Wheatfield, NY • 1-800-688-0030 • www.viatran.com • solutions@viatran.com



An ISO 9001: 2008 Certified Company

SPECIFICATIONS

Performance

Full Scale Pressure Range (FSPR)	0-5, 10, 20, 50, 100, 300, 750" W.C. 0-15, 50, 100 PSIG
Non-Linearity (Best Fit Straight Line)	≤ ±0.15% FSO
Hysteresis & Repeatability	≤ ±0.10% FSO
Full Scale Output (FSO)	
Model 244	5 VDC at 70° F
Model 344	16 mA at 70° F
Resolution	Infinite
Long Term Stability	≤ ± 0.2% FSO per 6 months
Zero Shift After 500 PSI Overload	≤ ± 0.1% FSO
Compensated Temperature Range	+70° F to +170° F
Operating Temperature Range	0° F to +250° F
Storage Temperature Range	-40° F to +250° F
Temperature Effect on Zero	≤ ± 2.0% FSO per 100° F
Temperature Effect on Span	≤ ± 2.0% FSO per 100° F

Electrical

Supply Voltage	10 to 42 VDC
Power Supply Regulation	≤ ± 0.1% FSO change over the supply voltage range
Output Signal	
Model 244	0 to 5 VDC standard (see option DM)
Model 344	4 to 20 mA
Output Loading (Model 244)	3000 Ohms minimum
Load Impedance (Model 344)	1600 Ohms with input voltage change from 10 to 42 VDC
Zero Adjustment	
Model 244	± 10% FSO minimum
Model 344	± 5% FSO minimum
Span Adjustment	
Model 244	± 10% FSO minimum
Model 344	± 10% FSO minimum
Calibration Signal	80% of the FSPR, by shorting pins - see Electrical Connections
Calibration Signal Accuracy	≤ ± 0.5% FSO
Circuit Protection	Reverse polarity protected
Insulation Resistance	<1nS
Response Time	From 0.2 Sec for 5" W.C. range down to 0.008 Sec for 100 PSI range. Faster response available with NF option.
Electrical Connections	Bendix PT02E-10-6P, mates with PT06E-10-6S (SR)
Pin A	Model 244 + Power Model 344 + Power / Signal
Pin B	- Power - Power / Signal
Pin C	+ Signal Calibrate
Pin D	- Signal Calibrate
Pin E	Calibrate N/C
Pin F	Calibrate N/C

Mechanical

Pressure Connections	1/4" NPT Female
Proof Pressure	500 PSI
Burst Pressure	1000 PSI
Position Sensitivity	≤ ± 1.0" W.C. in any orientation
Shock & Vibration	≤ ± 1.0% FSO per G for 50 Hz to 200 Hz along any axis
Fill Fluid	Dow DC200 Silicone oil
Mounting	May be supported by process piping or by optional mounting bracket
Materials of Construction	
Housing	304 and 316 Stainless Steel with a Cadmium plated electrical connector
Wetted Parts	316 Stainless steel
Weight	3.6 lbs.
Identification	Laser etched onto body

Options

Code	<i>Alternate Electrical Connectors</i>
BA	(K)PTIH-12-8P
BF	(K)PTIH-10-6P
BG	DIN 43650 344 Only
BI	CF3102E-14S-2P 344 Only
BK	WK4-32S 344 Only
BL	WK6-32S
BM	WKA7-32S
BN	(K)PTIH-8-4P 344 Only
BQ	(K)PTO2H-10-6P
BR	CF3102E-14S-6P
BS	CF3102E-14S-5P 344 Only
ZS	(K)PTO2E-10-6P
ZV	C31-10-6P-20-OP1 (SS)
	<i>Performance options</i>
DG	Improved temperature compensation to ±1.0% FSO per 100°F
DH	Special ranging
DK	Special calibration setting
DM	Modified full scale output (Model 244 only)
DQ	Cleaning for Oxygen service
EA	Calibration run at specified temperature
NF	Fast response time
NH	Stainless steel identification tag
NM	Alternate output signal(3mV/V) (Model 244 only)
PW	1/8 DIN Digital Indicator
	<i>Alternate Pressure Ports</i>
YA	MS 33649-04
YH	1/8 NPT(M)
YI	1/8 NPT(F)
YK	1/4 NPT(M)
YN	3/8 NPT(F)

Accessories

Digital Indicator
Mating electrical assembly
Mounting bracket

